

Hinge Gate Urinal



Hinge Gate Urinals are used in schools, sports stadiums and entertainment venues where there is a high demand in a short period of time. The urinal incorporates a floor grate that can be lifted for easy cleaning. The waste outlet can be positioned almost anywhere in the base of the urinal and the water inlet can be either a top entry to suit an on the wall cistern or a rear entry to suit a concealed system or automated flushing.

Technical Data

Product	Hinge Gate Urinal	
Type of Urinal	Slab Urinal	
Material	Gr304 Stainless Steel	
Material Thickness	1.2mm	
Material Surface Finish	Satin Finished	
Type of mounting	free standing on feet	Can be recessed into floor
		Step up (165mm) please request front skirt.
Inlet size	38mm	Top inlet
		Rear inlet
Outlet Size	DN50 (50 BSP)	
	DN90	
Overall Width	Minimum: 600mm	
	Maximum: 3600mm	
Overall Height	1115mm from step	
Overall Depth	610mm	
WELS approval	With cistern: 1.6	
	With Auto Flushing: 1.9	
Options	Free standing end (275mm)	
	Full width return ends (610mm)	
	Free standing end (610mm)	

The information in this sheet reflects the current technical specifications at the time of publication. As part of our continuous improvement program, we reserve the right to change the technical or physical specifications without notice.



Hinge Gate Urinal



←
Hinge gate urinal showing optional free standing end.

