

Outdoor Channel Specifications Sheet

Merchant details:


Merchant Name: _____

Contact Person: _____ Order No: _____ Phone: _____


Fax: _____ Please note: A purchase order is required before processing.

1. Channel profile

Safety Edge




Flange Only



Floor tile thickness = _____ mm

Upstand



Floor tile thickness = _____ mm

Wall tile thickness = _____ mm

Tiling upstands = (please mark)

Rear

Left  Right

2. Grate pattern

Angle



Brick



3. Select channel width

OC100 (grate width 100mm)

1: Outlet Size: DN 40 DN 50 DN 80

2. Depth at waste: select from 30mm - 65mm

Depth = _____mm

OC75 (grate width 75mm)

1: Outlet Size: DN 40 DN 50

2. Depth at waste: select from 25mm - 50mm

Depth = _____mm

OC50 (grate width 50mm)

1: Outlet Size: DN 40

2. Depth at waste: select from 20mm - 35mm

Depth = _____mm

4. Overall channel length

Length = _____mm

NOTE: Overall Length includes tiling flange width to either end.

5. Outlet position

Centered in channel length

Number of required outlets _____

1. Distance from LEFT end _____ mm

2. Distance from LEFT end _____ mm

3. Distance from LEFT end _____ mm

veitch

stainless steel
products

Tel: (03) 9465 4131
Fax: (03) 9465 1478

www.veitchstainless.com.au
enquiries@veitchstainless.com.au